



DNB ENGINEERING

Testing and Engineering Services

LISN DB4111

Product Information

Version 0.1

08/27/2019

Document Number: PI-DB4111-001

1. Description

The DB4111 line impedance stabilization network (LISN) are designed to meet the requirements of RTCA DO-160 (with external 10uF capacitor), and MIL-STD-461G Appendix A specifications. LISN's are available in multiple configurations and a wide variety of terminations. Additional customizations can be made at request including voltage, current ratings, number of circuits, etc.

Inductance:	5 μ H
Frequency Range:	150kHz – 400MHz
Current Ratings:	15A, 25A, 50A, 100A
Voltage Ratings:	DC – 800V, 60Hz – 480VAC, 400Hz – 270VAC, 800Hz – 130VAC
Circuits:	Single, Double
RF Connector:	BNC, N
Terminations:	Binding Post (5 way), Supercon, Receptacles*

2. Catalog

PN	Type	Inductance	Current	Termination	RF Connector
DB4111S-5-15-BP-B	Single	5uH	15A	Binding Post	BNC
DB4111S-5-15-BP-N	Single	5uH	15A	Binding Post	N
DB4111S-5-15-SC-B	Single	5uH	15A	Supercon	BNC
DB4111S-5-15-SC-N	Single	5uH	15A	Supercon	N
DB4111S-5-25-BP-B	Single	5uH	25A	Binding Post	BNC
DB4111S-5-25-BP-N	Single	5uH	25A	Binding Post	N
DB4111S-5-25-SC-B	Single	5uH	25A	Supercon	BNC
DB4111S-5-25-SC-N	Single	5uH	25A	Supercon	N
DB4111S-5-50-SC-N	Single	5uH	50A	Supercon	N
DB4111S-5-100-SC-N	Single	5uH	100A	Supercon	N
DB4111D-5-15-BP-B	Dual	5uH	15A	Binding Post	BNC
DB4111D-5-15-BP-N	Dual	5uH	15A	Binding Post	N
DB4111D-5-15-SC-B	Dual	5uH	15A	Supercon	BNC
DB4111D-5-15-SC-N	Dual	5uH	15A	Supercon	N
DB4111D-5-15-RX-B	Dual	5uH	15A	Receptacle*	BNC
DB4111D-5-15-RX-N	Dual	5uH	15A	Receptacle*	N
DB4111D-5-25-BP-B	Dual	5uH	25A	Binding Post	BNC
DB4111D-5-25-BP-N	Dual	5uH	25A	Binding Post	N
DB4111D-5-25-SC-B	Dual	5uH	25A	Supercon	BNC
DB4111D-5-25-SC-N	Dual	5uH	25A	Supercon	N
DB4111D-5-25-RX-B	Dual	5uH	25A	Receptacle*	BNC
DB4111D-5-25-RX-N	Dual	5uH	25A	Receptacle*	N
DB4111D-5-50-SC-N	Dual	5uH	50A	Supercon	N
DB4111D-5-50-RX-N	Dual	5uH	50A	Receptacle*	N
DB4111D-5-100-SC-N	Dual	5uH	100A	Supercon	N
DB4111D-5-100-RX-N	Dual	5uH	100A	Receptacle*	N